



FLEXIBLE FLOODLIGHT

LIGHTING SERIES

The RESQTEC flexible flood light series provide sufficient lighting during rescue operations. Engineered for quick response by Fire, Police, Ambulance, Public Works and tow truck operators. The robotic arm operated by handheld controller allows for quick positioning and is unique in its ability to be fully directional; tilt 180 and turn by 360 degrees. The high volume of light also supports the warming of personnel/victim(s).



COMMAND LIGHT SHADOW

SL442A-FS

SL445A-LF

Description	4 x 220 W AC-Spectra LED	4 x 500 Watt
Voltage	12 V + 115V	12 V + 115V
Power requirements	1.000 Watts	2.000 Watts
Dimensions nested H x W x D	230 x 1220 x 815 mm	230 x 1220 x 610 mm
Dimensions upright H x W x D	1260 x 1320 x 815 mm	1260 x 1320 x 610 mm
Total Watts	880 Watts	2.000 Watts
Output	80.000 Lumens	44.400 Lumens
Weight	35 kg	35 kg



COMMAND LIGHT KNIGHT

KL415A-FS

KL450A-LF

Voltage	115/230	115/230
Power requirements	1.500 Watts	3.000 Watts
Dimensions nested H x W x D	355 x 1195 x 890 mm	330 x 1195 x 660 mm
Dimensions upright H x W x D	2225 x 1320 x 890 mm	2225 x 1320 x 660 mm
Total Watts	1.320 Watts	3.000 Watts
Output	120.000 Lumens	66.600 Lumens
Weight	75 kg	75 kg



COMMAND LIGHT

CL602A-FS

CL607A-HQ

Voltage	115/230	115/230
Power requirements	1.500 Watts	4.500 Watts
Dimensions nested H x W x D	305 x 1880 x 1120 mm	305 x 1880 x 1065 mm
Dimensions upright H x W x D	3330 x 2010 x 1120 mm	3330 x 2010 x 1065 mm
Total Watts	1.320 watts	5.000 Watts
Output	120.000 Lumens	99.000 Lumens
Weight	139 kg	139 kg

AIRBLAST VENTILATION SERIES

THE LATEST TECHNOLOGY IN FIRE ATTACK

Resqtec offers various types of ventilation equipment. For more information, specifications and types of units please contact your local distributor.



COMPACT AIRBLAST

	COMPACT 8"	COMPACT 8" EXPLOSION PROOF
Dimensions (L x W x H)	406 x 273 x 292 mm	406 x 273 x 292 mm
Motor	1/3 HP / 0.25 kW totally enclosed	1/3 HP / 0.25 kW hazardous location
Operational weight	9.1 kg	10.0 kg
Speed	3,450 RPM	3,450 RPM
Airflow	1,760 m ³ /hour	1,760 m ³ /hour
Open airflow ¹	2,745 m ³ /hour	2,745 m ³ /hour
Start	2,000 W	2,000 W
Run	700 W	700 W



NEGATIVE AIRBLAST

	16" VARIABLE SPEED	16" HONDA
Dimensions (L x W x H)	660 x 480 x 330 mm	500 x 490 x 400 mm
Motor	1 HP / 0.75 kW variable speed	Honda GX120
Operational weight	26 kg	25 kg
Speed	0 – 2,500 RPM	0 – 3,500 RPM
Airflow	10,024 m ³ /hour	15,715 m ³ /hour
Open airflow ¹	16,723 m ³ /hour	26,142 m ³ /hour
Start	1,500 W	N/A
Run	1,500 W	N/A



POSITIVE AIRBLAST 18"

	VARIABLE SPEED	HONDA GX
Dimensions (L x W x H)	610 x 560 x 560 mm	610 x 560 x 560 mm
Motor	1 HP / 0.75 kW variable speed	Honda GX 200 / 5.5 HP / 4.1 kW
Operational weight	34 kg	33 kg
Speed	2,400 RPM	3,535 RPM
Airflow	21,781 m ³ /hour	26,487 m ³ /hour
Open airflow ¹	35,863 m ³ /hour	48,230 m ³ /hour
Air cone guard	Yes	Yes
Tilting positions	7 positions	7 positions



POSITIVE AIRBLAST 20"

	VARIABLE SPEED	HONDA GX
Dimensions (L x W x H)	660 x 640 x 590 mm	660 x 640 x 590 mm
Motor	1 HP / 0.75 kW Variable speed	Honda GX 200 / 5.5 HP / 4.1 kW
Operational weight	34 kg	37 kg
Speed	2,400 RPM	3,535 RPM
Airflow	25,672 m ³ /hour	31,567 m ³ /hour
Open airflow ¹	41,267 m ³ /hour	50,186 m ³ /hour
Air cone guard	Yes	Yes
Tilting positions	7 positions	7 positions



¹Maximum is a theoretical flow